


Wrench Allen / Hex Key Inch


Item Number	Standard				Metric			
	Size (s)	Length (l)	Height (h)	Weight	Size (s)	Length (l)	Height (h)	Weight
916-710-02A	1/16"	1 1/2"	1/2"	0.011	-	38 mm	13 mm	0.005
916-710-04A	5/64"	1 1/2"	1/2"	0.011	-	38 mm	13 mm	0.005
916-710-06A	3/32"	1 1/2"	1/2"	0.011	-	38 mm	13 mm	0.005
916-710-08A	7/64"	2 3/8"	1"	0.011	-	58 mm	24 mm	0.005
916-710-10A	1/8"	2 3/8"	1"	0.013	-	58 mm	24 mm	0.006
916-710-12A	9/64"	2 1/2"	1 1/8"	0.015	-	64 mm	29 mm	0.007
916-710-14A	5/32"	2 1/2"	1 3/16"	0.020	-	65 mm	30 mm	0.009
916-710-16A	3/16"	1 1/8"	1 1/4"	0.031	-	79 mm	31 mm	0.014
916-710-18A	7/32"	3 3/8"	1 1/2"	0.040	-	85 mm	37 mm	0.018
916-710-20A	1/4"	3 3/8"	1 1/2"	0.060	-	85 mm	37 mm	0.027
916-710-22A	9/32"	3 1/2"	1 11/16"	0.088	-	88 mm	43 mm	0.040
916-710-24A	5/16"	3 5/8"	1 3/4"	0.097	-	92 mm	44 mm	0.044
916-710-26A	11/32"	3 3/4"	1 3/4"	0.099	-	97 mm	44 mm	0.045
916-710-28A	3/8"	4 5/16"	1 3/4"	0.176	-	110 mm	45 mm	0.080
916-710-30A	7/16"	4 11/16"	1 7/8"	0.220	-	119 mm	48 mm	0.100
916-710-32A	1/2"	5 1/2"	1 3/16"	0.342	-	140 mm	55 mm	0.155
916-710-34A	9/16"	6"	2 1/4"	0.397	-	150 mm	58 mm	0.180
916-710-36A	5/8"	6 3/8"	2 1/2"	0.540	-	162 mm	63 mm	0.245
916-710-38A	11/16"	6 5/8"	2 5/8"	0.717	-	168 mm	65 mm	0.325
916-710-40A	3/4"	7"	2 5/8"	0.915	-	178 mm	73 mm	0.415
916-710-42A	13/16"	7 1/4"	3"	1.146	-	184 mm	77 mm	0.520
916-710-44A	7/8"	37 3/8"	3 1/8"	1.312	-	187 mm	79 mm	0.595
916-710-46A	15/16"	7 1/2"	3 1/4"	1.665	-	192 mm	82 mm	0.755
916-710-48A	1"	8"	3 3/8"	1.852	-	200 mm	85 mm	0.840
916-710-50A	1 1/16"	8 3/8"	3 11/16"	2.458	-	213 mm	93 mm	1.115



Wrench Allen / Hex Key with Ball Inch*


Item Number	Standard				Metric			
	Size (s)	Length (l)	Height (h)	Weight	Size (s)	Length (l)	Height (h)	Weight
916-7A1-02B	3/32"	2"	1/2"	0.007	-	50 mm	16 mm	0.003
916-7A1-03B	1/8"	2 1/2"	3/4"	0.011	-	63 mm	20 mm	0.005
916-7A1-04B	5/32"	2 3/4"	1"	0.026	-	70 mm	25 mm	0.012
916-7A1-05B	3/16"	3 3/16"	1 1/16"	0.049	-	80 mm	28 mm	0.022
916-7A1-06B	1/4"	3 1/2"	1 1/4"	0.066	-	90 mm	32 mm	0.030
916-7A1-08B	5/16"	3 7/8"	1 7/16"	0.123	-	100 mm	36 mm	0.056
916-7A1-10B	3/8"	4 5/8"	1 5/8"	0.309	-	118 mm	42 mm	0.140
916-7A1-12B	1/2"	4 7/8"	1 3/4"	0.357	-	125 mm	45 mm	0.162

*Only Available in Beryllium Copper at this time



Wrench Allen / Hex Key Metric


Item Number	Metric				Standard			
	Size (s)	Length (l)	Height (h)	Weight	Size (s)	Length (l)	Height (h)	Weight
901-660-15A	1.5 mm	38 mm	13 mm	0.005	-	1 1/2"	1/2"	0.011
901-660-20A	2 mm	38 mm	13 mm	0.005	-	1 1/2"	1/2"	0.011
901-660-25A	2.5 mm	38 mm	13 mm	0.005	-	1 1/2"	1/2"	0.011
901-660-30A	3 mm	59 mm	25 mm	0.007	-	2 3/8"	1"	0.015
901-660-40A	4 mm	65 mm	30 mm	0.008	-	2 1/2"	1 3/16"	0.018
901-660-50A	5 mm	79 mm	32 mm	0.012	-	1 1/8"	1 1/4"	0.026
901-660-60A	6 mm	85 mm	37 mm	0.020	-	3 3/8"	1 1/2"	0.044
901-660-70A	7 mm	88 mm	43 mm	0.030	-	3 1/2"	1 11/16"	0.066
901-660-80A	8 mm	92 mm	44 mm	0.045	-	3 5/8"	1 3/4"	0.099
901-660-90A	9 mm	97 mm	44 mm	0.055	-	3 3/4"	1 3/4"	0.121
901-661-00A	10 mm	110 mm	45 mm	0.070	-	4 5/16"	1 3/4"	0.154
901-661-10A	11 mm	119 mm	48 mm	0.090	-	4 11/16"	1 7/8"	0.198
901-661-20A	12 mm	130 mm	52 mm	0.130	-	5 1/8"	2"	0.287
901-661-30A	13 mm	140 mm	54 mm	0.160	-	5 1/2"	2 1/8"	0.353
901-661-40A	14 mm	150 mm	58 mm	0.191	-	6"	2 1/4"	0.421
901-661-50A	15 mm	156 mm	60 mm	0.230	-	6 1/8"	2 3/8"	0.507
901-661-60A	16 mm	162 mm	63 mm	0.270	-	6 3/8"	2 1/2"	0.595
901-661-70A	17 mm	168 mm	65 mm	0.335	-	6 5/8"	2 5/8"	0.739
901-661-80A	18 mm	173 mm	69 mm	0.402	-	6 13/16"	2 3/4"	0.886
901-661-90A	19 mm	177 mm	72 mm	0.445	-	7"	2 13/16"	0.981
901-662-10A	21 mm	184 mm	74 mm	0.595	-	7 1/4"	2 7/8"	1.312
901-662-20A	22 mm	186 mm	77 mm	0.615	-	7 5/16"	3"	1.356
901-662-40A	24 mm	192 mm	82 mm	0.755	-	7 1/2"	3 1/4"	1.665
901-662-50A	25 mm	200 mm	81 mm	0.840	-	8"	3 3/16"	1.852
901-662-60A	26 mm	206 mm	90 mm	0.940	-	8 1/8"	3 1/2"	2.072
901-662-70A	27 mm	213 mm	93 mm	1.115	-	8 3/8"	3 11/16"	2.458
901-662-80A	28 mm	222 mm	95 mm	1.235	-	8 3/4"	3 3/4"	2.723
901-663-00A	30 mm	240 mm	105 mm	1.475	-	9 1/2"	4 1/8"	3.252
901-663-20A	32 mm	266 mm	116 mm	1.885	-	10 1/2"	4 1/2"	4.156
901-663-60A	36 mm	294 mm	128 mm	2.650	-	11 1/2"	5"	5.842
901-664-10A	41 mm	320 mm	140 mm	3.760	-	12 1/2"	5 1/2"	8.290



Wrench Allen / Hex Key with Ball Metric*


Item Number	Metric				Standard			
	Size (s)	Length (l)	Height (h)	Weight	Size (s)	Length (l)	Height (h)	Weight
916-7B1-02B	2 mm	50 mm	16 mm	0.003	-	2"	1/2"	0.007
916-7B1-03B	3mm	63 mm	20 mm	0.005	-	2 1/2"	3/4"	0.011
916-7B1-04B	4 mm	70 mm	25 mm	0.012	-	2 3/4"	1"	0.026
916-7B1-05B	5 mm	80 mm	28 mm	0.022	-	3 3/16"	1 1/16"	0.049
916-7B1-06B	6 mm	90 mm	32 mm	0.030	-	3 1/2"	1 1/4"	0.066
916-7B1-07B	7 mm	95 mm	34 mm	0.050	-	3 3/4"	1 3/5"	0.110
916-7B1-08B	8 mm	100 mm	36 mm	0.056	-	3 7/8"	1 7/16"	0.123
916-7B1-09B	9 mm	106 mm	38 mm	0.085	-	4 1/8"	1 1/2"	0.187
916-7B1-10B	10 mm	112 mm	40 mm	0.100	-	4 3/8"	1 9/16"	0.220
916-7B1-11B	11 mm	118 mm	42 mm	0.140	-	4 5/8"	1 5/8"	0.309
916-7B1-12B	12 mm	125 mm	45 mm	0.162	-	4 7/8"	1 3/4"	0.357

*Only Available in Beryllium Copper at this time




Screwdriver Insulated Slotted

Item Number	Standard					Metric				
	Length (l)	Shaft (b)	Blade (a)	Thickness (t)	Weight	Length (l)	Shaft (b)	Blade (a)	Thickness (t)	Weight
926-510-06A	6 1/8"	3"	1/8"	0.015"	0.071	157 mm	75 mm	3 mm	0.4 mm	0.032
926-510-12A	7 5/32"	4"	5/32"	0.020"	0.093	182 mm	100 mm	4 mm	0.5 mm	0.042
926-510-18A	9 5/16"	5"	1/4"	0.030"	0.209	237 mm	125 mm	6 mm	0.8 mm	0.095
926-510-22A	10 5/16"	6"	17/64"	0.040	0.265	262 mm	150 mm	7 mm	1.0 mm	0.120
926-510-26A	12 1/4"	8"	5/16"	0.047"	0.342	312 mm	200 mm	8 mm	1.2 mm	0.155
926-510-28A	14 1/4"	10"	3/8"	0.055"	0.386	362 mm	250 mm	9 mm	1.4 mm	0.175
926-510-32A	16 1/4"	12"	13/32"	0.071"	0.507	412 mm	300 mm	10 mm	1.8 mm	0.230
926-510-38A	21 5/8"	16"	1/2"	0.094"	0.948	550 mm	400 mm	12 mm	2.4 mm	0.430




Screwdriver Insulated Phillips

Item Number	Standard				Metric			
	Length (l)	Shaft (b)	Blade (a)	Weight	Length (l)	Shaft (b)	Blade (a)	Weight
926-610-02A	5 3/16"	3"	#0	0.071	132 mm	75 mm	#0	0.032
926-610-06A	8"	4"	#2	0.154	203 mm	100 mm	#2	0.070
926-610-08A	9 5/16"	5"	#2	0.209	237 mm	125 mm	#2	0.095
926-610-10A	10 5/16"	6"	#2	0.231	262 mm	150 mm	#2	0.105
926-610-12A	12 1/4"	8"	#3	0.342	312 mm	200 mm	#3	0.155
926-610-16A	16 1/4"	12"	#4	0.507	412 mm	300 mm	#4	0.230




Screwdriver Slotted

Item Number	Standard					Metric				
	Length (l)	Shaft (b)	Blade (a)	Thickness (t)	Weight	Length (l)	Shaft (b)	Blade (a)	Thickness (t)	Weight
926-010-06A	6 1/8"	3"	1/8"	0.015"	0.071	157 mm	75 mm	3 mm	0.4 mm	0.032
926-010-12A	7 5/32"	4"	5/32"	0.020"	0.093	182 mm	100 mm	4 mm	0.5 mm	0.042
926-010-20A	10 5/16"	6"	1/4"	0.040	0.231	262 mm	150 mm	6 mm	1.0 mm	0.105
926-010-26A	12 1/4"	8"	5/16"	0.047"	0.342	312 mm	200 mm	8 mm	1.2 mm	0.155
926-010-28A	14 1/4"	10"	3/8"	0.055"	0.386	362 mm	250 mm	9 mm	1.4 mm	0.175
926-010-32A	16 1/4"	12"	13/32"	0.071"	0.507	412 mm	300 mm	10 mm	1.8 mm	0.230
926-010-36A	18 3/16"	14"	7/16"	0.079"	0.661	462 mm	350 mm	11 mm	2.0 mm	0.300
926-010-38A	21 5/8"	16"	1/2"	0.094"	0.948	550 mm	400 mm	12 mm	2.4 mm	0.430




Screwdriver Phillips

Item Number	Standard				Metric			
	Length (l)	Shaft (b)	Blade (a)	Weight	Length (l)	Shaft (b)	Blade (a)	Weight
926-110-02A	5 3/16"	2"	#0	0.071	132 mm	50 mm	#0	0.032
926-110-04A	7"	3"	#1	0.139	178 mm	75 mm	#1	0.063
926-110-08A	9 3/8"	5"	#2	0.209	237 mm	125 mm	#2	0.095
926-110-12A	12 1/4"	8"	#2	0.342	312 mm	200 mm	#2	0.155
926-110-16A	16 1/4"	12"	#3	0.507	412 mm	300 mm	#3	0.230
926-110-20A	21 5/8"	16"	#4	0.617	550 mm	400 mm	#4	0.280




Screwdriver Electrician

Item Number	Standard					Metric				
	Length (l)	Shaft (b)	Blade (a)	Thickness (t)	Weight	Length (l)	Shaft (b)	Blade (a)	Thickness (t)	Weight
926-3A1-02A	5 3/16"	2"	1/8"	0.015"	0.077	132 mm	50 mm	3 mm	0.4 mm	0.035
926-3A1-04A	7 5/32"	4"	5/32"	0.020"	0.099	182 mm	100 mm	4 mm	0.5 mm	0.045
926-3A1-06A	8"	4"	1/4"	0.030"	0.198	204 mm	100 mm	6 mm	0.8 mm	0.090
926-3A1-08A	10 5/16"	6"	5/16"	0.047"	0.298	262 mm	150 mm	8 mm	1.2 mm	0.135
926-3A1-10A	12 1/4"	8"	13/32"	0.071"	0.463	312 mm	200 mm	10 mm	1.8 mm	0.210



Screwdriver Pozidrive

Item Number	Standard				Metric			
	Length (l)	Shaft (b)	Blade (a)	Weight	Length (l)	Shaft (b)	Blade (a)	Weight
926-410-02A	5 3/16"	2"	#0	0.073	132 mm	50 mm	#0	0.033
926-410-04A	6 1/8"	3"	#1	0.093	157 mm	75 mm	#1	0.042
926-410-06A	8 3/8"	4"	#2	0.176	212 mm	100 mm	#2	0.080
926-410-08A	10 5/16"	6"	#3	0.298	262 mm	150 mm	#3	0.135
926-410-10A	12 1/4"	8"	#4	0.463	312 mm	200 mm	#4	0.210



Screwdriver Torx

Item Number	Standard				Metric			
	Length (l)	Shaft (b)	Blade (a)	Weight	Length (l)	Shaft (b)	Blade (a)	Weight
926-4A1-02A	7"	3"	T10	0.139	178 mm	75 mm	T10	0.063
926-4A1-04A	7"	3"	T15	0.139	178 mm	75 mm	T15	0.063
926-4A1-06A	8"	4"	T20	0.209	203 mm	100 mm	T20	0.095
926-4A1-08A	9 5/16"	5"	T25	0.220	257 mm	125 mm	T25	0.100
926-4A1-10A	10 5/16"	6"	T30	0.220	262 mm	150 mm	T30	0.100
926-4A1-12A	12 1/4"	8"	T40	0.342	312 mm	200 mm	T40	0.155
926-4A1-14A	14 1/4"	10"	T45	0.386	362 mm	250 mm	T45	0.175
926-4A1-16A	16 5/16"	12"	T50	0.430	415 mm	300 mm	T50	0.195
926-4A1-18A	18 3/16"	14"	T55	0.496	462 mm	350 mm	T55	0.225
926-4A1-20A	20 1/8"	16"	T60	0.496	512 mm	400 mm	T60	0.225

