

REMS Magnum

Threading Roll Grooving



Magnum T



REMS Magnum – the compact up to 2"!

■ Only 1 universal automatic die head from 1/16-2" for all threads ■ Automatic lubrication and cooling ■ Proven quick-action hammer chuck ■ Large oil basin and chip tray ■ Maintenance-free gear ■ Choice of 3 motors

REMS Magnum. Threading, cutting, deburring, nipple threading. Pipe threads 1/16–2", bolt threads 6–60 mm, 1/4-2". Machine complete with dies NPT 1/2-3/4", NPT 1–2". Model L-T is a light version with removable large oil basin and chip tray. Model T with integrated, even larger oil basin and chip tray. For workbench, stand, collapsible wheel stand or wheel stand with material shelf.

2000 T Universal motor 110 V, 50-60 Hz, 1700 W (2.31 HP). 53 rpm.

Art.-No. 340220

2010 T Pole-reversible capacitor motor 110 V, 60 Hz, 2100 W (2.85 HP).

30 rpm, also under full load. Very quiet running. Art.-No. 340221

2000 L-T Universal motor 110 V. 50-60 Hz. 1700 W (2.31 HP).

Art.-No. 340226

2010 L-T Pole-reversible capacitor motor 110 V, 60 Hz, 2100 W (2.85 HP).

Art.-No. 340227 30 rpm, also under full load. Very quiet running.

REMS Magnum – the super machine up to 3"!

available on special order

REMS Magnum – the super machine up to 4"!

 \blacksquare Only 1 universal automatic die head from $\frac{1}{4}$ -2" and from $\frac{2}{2}$ -4" for all threads

Exceptionally round and clean threads up to 4" by using 6 threading dies

■ Automatic lubrication and cooling ■ Proven quick-action hammer chuck ■ Large oil basin and chip tray \blacksquare Maintenance-free gear

REMS Magnum. Threading, cutting, deburring, nipple threading. Pipe threads $\frac{1}{4}$ -4", bolt threads 14-60 mm, $\frac{1}{2}-2$ ". Machine complete with dies for NPT pipe threads. Integrated, even larger oil basin and chip tray. For workbench, stand, collapsible wheel stand or wheel stand with material shelf.

4000 T Universal motor 110 V, 50-60 Hz, 1700 W (2.31 HP). 23 rpm.

> Equipment 21/2-4" Art.-No. 380426 Equipment ½-4" Art.-No. 380429

4020 T Pole-reversible 3 phase motor 220 V, 60 Hz, 2000 W (2.72 HP).

24/12 rpm, also under full load. Very quiet running.

Equipment 2½-4" Art.-No. 380428

Equipment 1/2-4" Art.-No. 380431









Collapsible wheel stand

Universal motor

Capacitor motor

3-phase motor



Made in Germany



Wheel stand

(accessory)





Stand Art.-No. 344105 Wheel stand with material shelf Art.-No. 344100

