



Made in Germany



## REMS Hydro-Swing – effortless working due to oil-hydraulic force transmission!

- Robust, compact drive unit with closed, maintenance-free hydraulic system.
- Universal use for many tubes n Handy and light, only 2.4 kg (5.3 lbs) ■ Proven, reliable ratchet feed ■ Simple, fast operation, e.g. bends  $\varnothing$  22 mm ( $\frac{7}{8}$ " ) in only 18 s ■ Only 1 bender drive for the complete work range up to  $\varnothing$  32 mm ■ Marked bending formers for exact bending ■ Crossover, swan-neck, reverse bends possible ■ Easy and rapid changing of bending formers ■ Reliable hydraulic thrust with overload protection ■ Bender recovered after a few bends through savings on fittings

**REMS Hydro-Swing Set.** Oil-hydraulic hand pipe bender  $\varnothing$  10–32 mm,  $\frac{3}{8}$ – $\frac{7}{8}$ " , up to 90°. Soft copper pipes  $\varnothing$  10–22 mm,  $\frac{3}{8}$ – $\frac{7}{8}$ " ,  $s \leq 1$  mm, soft, coated copper pipes  $\varnothing$  10–18 mm,  $\frac{3}{8}$ – $\frac{7}{8}$ " ,  $s \leq 1$  mm, pipes of the pressfitting systems made of stainless steel  $\varnothing$  12–22 mm,  $s \leq 1.2$  mm, soft, coated carbon steel  $\varnothing$  12–18 mm,  $s \leq 1.2$  mm, soft precision steel pipes  $\varnothing$  10–22 mm,  $s \leq 1.5$  mm, composite tubes  $\varnothing$  14–32 mm. Up to  $\varnothing$  26 mm with drive unit, bending formers, back former support H-S  $\varnothing$  10–26 mm with back formers, Allen key, in a sturdy steel case. Up to  $\varnothing$  32 mm with drive unit, bending formers, 2 back former supports  $\varnothing$  10–26 mm and  $\varnothing$  32 mm with back formers, Allen key, in a sturdy steel case.

**Set 3/8-1/2-5/8-3/4-7/8" Art.-No. 153521**

for soft copper tubes, stainless steel tubes

**Set 16-20-25/26-32 Art.-No. 153529**

for multi-layer composite tubes

**Set Allround 32**

**10-12-14-15-16-17-18-20-22-25/26-32**

**$\frac{3}{8}$ - $\frac{1}{2}$ - $\frac{5}{8}$ - $\frac{3}{4}$ - $\frac{7}{8}$ "**

**Art.-No. 153528**

Tested by electrouisse >>

Made in Germany



For hard copper tubes, also half hard or thin-wall, up to  $\varnothing$  1 $\frac{3}{8}$ " O.D.



WB



3B



## REMS Curvo – wrinkle-free bending!

- Universal for many pipes and tubes ■ Compact, with integral absorption of torque during bending ■ Super light, drive unit only 8 kg (17.6 lbs) ■ Can be used anywhere without previous setting ■ Fast and creep speed operation for precise bending, e.g. 90° bends,  $\frac{3}{8}$ " in only 6 s. ■ Angle scale 0 to 180° ■ Rapid change of bending and back formers ■ Only one type of bending and back formers for REMS Curvo, REMS Curvo 50 and REMS Akku-Curvo ■ Maintenance-free gear with safety slipping clutch ■ Universal motor 110 V, 50–60 Hz, 1000 W (1.36 HP) ■ Bender recovered after a small number of bends through savings on fittings

**REMS Curvo Set.** Electric pipe bender  $\varnothing$  10–40 mm,  $\frac{3}{8}$ –1 $\frac{1}{8}$ " , up to 180°. Hard, half-hard and soft tubes, also thin-walled,  $\varnothing$  10–35 mm,  $\frac{3}{8}$ –1 $\frac{1}{8}$ " , coated soft copper tubes, also thin-walled,  $\varnothing$  10–18 mm, stainless steel tubes of pressfitting systems  $\varnothing$  12–28 mm,  $\frac{3}{8}$ –1 $\frac{1}{8}$ " , coated steel tubes of pressfitting system mpress C-STAHl  $\varnothing$  12–28 mm, soft precision steel tubes  $\varnothing$  10–30 mm, steel pipes  $\frac{1}{2}$ – $\frac{3}{4}$ " , conduit DIN EN 50086  $\varnothing$  16–32 mm, composite tubes  $\varnothing$  14–40 mm, and others. Drive unit, insert bolt. Bending formers and back formers. In sturdy steel case.

**Set  $\frac{3}{8}$ - $\frac{1}{2}$ - $\frac{5}{8}$ - $\frac{3}{4}$ - $\frac{7}{8}$ " O.D.**

**Art.-No. 580024**

**Basic-Pack (without bending and back formers)**

**Art.-No. 580010**

### Accessories REMS Curvo

Machine support 3B height adjustable on tripod

Art.-No. 586100

Machine support WB, height adjustable, for mounting on work bench

Art.-No. 586150

REMS bending spray, 400 ml (14.1 oz)

Art.-No. 140120

Bending

Made in Germany

New



Made in Germany



## REMS Akku-Curvo 22 V – Cordless bending, wrinkle free up to 180°.

- Universal for many pipes and tubes ■ Compact, with integral absorption of torque during bending ■ Super light, drive unit only 8,5 kg (18.7 lbs) ■ Can be used anywhere without previous setting ■ Fast and creep speed operation for precise bending, e.g. 90° bends, Ø ¾" in only 6 s. ■ Angle scale 0 to 180° ■ Rapid change of bending and back formers ■ Only one type of bending and back formers for REMS Curvo, REMS Curvo 50 and REMS Akku-Curvo ■ Maintenance-free gear with safety slipping clutch ■ 500W battery motor ■ Bender recovered after a small number of bends through savings on fittings ■ Approx. 90 pipe bends of ¾" with one battery charge ■ Overheating protection and battery status check



**REMS Akku-Curvo 22V Basic-Pack.** Cordless tube bender Ø 10–40 mm, Ø ¼–1½", up to 180°. Hard, semi-hard, soft copper pipes, also thin-walled, Ø 10–28 mm, Ø ¾–1½", soft coated copper pipes, also thin-walled, Ø 10–18 mm, thick-walled copper pipes K65 for refrigeration and air conditioning technology EN 12735-1 Ø ¾–1½", pipes of the press fitting systems of stainless steel Ø 12–28 mm, carbon steel, also coated, Ø 12–28 mm, soft precision steel pipes Ø 10–28 mm, steel pipes EN 10255 Ø ¼–¾", electrical installation pipes EN 50086 Ø 16–25 mm, composite tubes Ø 14–40 mm, etc. Drive unit with maintenance-free gear and safety slipping clutch, powerful 21.6 V battery motor, stepless electronic safety switch, right and left-hand rotation, insert bolt. Machine status check with overload protection, temperature monitoring, battery charging status check. Li-Ion 21.6 V, 5.0 Ah, Li-Ion 110 V, 50–60 Hz, 90 W rapid charger. Without bending formers and back formers. In sturdy steel case. **Art.-No. 580014**  
**Set ¾ - ½" - ¾" - ¾" - ¾" O.D. Art.-No. 580066**

### Accessories for REMS Akku-Curvo 22 V:

Battery Li-Ion 21.6 V, 5.0 Ah	<b>Art.-No. 571581</b>
Battery Li-Ion 21.6 V, 9.0 Ah	<b>Art.-No. 571583</b>
Rapid charger Li-Ion 110 V, 50–60 Hz, 90 W	<b>Art.-No. 571585</b>

## REMS Curvo 50

Wrinkle free bending of large pipes!

- Universal, compact electric tool for cold bending of pipes and tubes up to 50 mm, 1½", up to 90° ■ All bending formers and back formers from REMS Curvo can be used ■ Simple, effortless, fast working, e.g. 90° bends of steel pipe Ø 1 ¼" in 37 s.

**REMS Curvo 50 Basic-Pack.** Electric pipe and tube bender Ø 10–50 mm, ¾–1½", up to 90°. Steel pipes Ø ¼–1½", hard, half-hard and soft copper tubes, Ø 10–42 mm, ¾–1½", stainless steel tubes of pressfitting systems Ø 12–42 mm, ¾–1½", multi-layer composite tubes Ø 14–50 mm and others. Drive unit with maintenance-free gear and safety slipping clutch, universal motor 110 V, 50–60 Hz, 1000 W (1.36 HP), stepless electronic safety switch, right and left-hand rotation. Adaptor block 35–50, Support 35–50, insert bolt. In sturdy carrying case. **Art.-No. 580110**  
**Adaptor block 10–40, Support 10–40, ¾–1½"**  
**for bending formers and back formers REMS Curvo Art.-No. 582120**





